


## PREMIUM, DURABLE PERFORMANCE FOR DEMANDING REGIONAL HAUL AND IN-CITY APPLICATIONS.

Durability and high performance under the toughest regional haul and in-city conditions are the hallmarks of the RY023. This sure-footed, five-rib, all-position workhorse features a tough band of additional rubber that protects the sidewall from scrubbing damage caused by curbing and other regional haul and in-city application abuses.


### Enhanced Durability

**Rock-ejector platforms** keep stones and debris out of the grooves to help thwart irregular wear and enhance durability.



Rock-Ejector Platforms


**Sidewall abrasion guard**, a tough band of additional rubber, reduces damage to the sidewall caused by curbing and other accidental scrubbing.



Sidewall Abrasion Guard

### Long Wearing Design


**Five-rib tread pattern** with semi-rounded shoulders reduces the potential for shoulder ripping and tearing while enhancing lateral stability, water dispersion and overall traction.



Tread Pattern

### Mounting Ease

**Hexagonal bead base** allows for easier mounting and even pressure along the entire circumference of the wheel for smooth rolling as well as increased driver comfort.



Hexagonal Bead

### PURE YOKOHAMA TECHNOLOGY

RY023 is equipped with the best Yokohama premium design concepts to meet stringent, modern fleet performance demands.



# RYO23

## SPECIFICATIONS

Tire Size	Part #	Ply Rating (L.R.)	Rim Size		Inflated Dimensions			Loaded Dimensions			Rev./Mile
			Meas.	Alt.	Overall Width (Inch)	Overall Diameter (Inch)	Groove Depth (1/32")	Section Width (Inch)	Static Radius (Inch)		
215/75R17.5	02385*	16H	6.00	6.00 - 6.75	8.5	30.6	16	9.1	14.2	674	
235/75R17.5	02386*	16H	6.75	6.75 - 7.50	9.4	31.7	16	10.0	14.6	661	
225/70R19.5	02389	12F	6.75	6.00	8.7	31.8	16	9.4	14.8	652	
245/70R19.5	02399	14G	7.50	6.75	9.7	33.3	16	10.4	15.5	628	
265/70R19.5	02398	14G	7.50	8.25	10.3	34.3	17	11.1	15.8	612	
285/70R19.5	02397	16H	8.25	7.50 - 9.00	11.1	35.1	17	12.1	16.3	597	
255/70R22.5	02387	16H	7.50	8.25	10.1	36.6	18	10.7	17.1	570	
295/75R22.5	02396	14G	9.00	8.25	11.1	40.2	19	12.1	18.7	520	
295/75R22.5	02391	16H	9.00	8.25	11.1	40.2	19	12.1	18.7	520	
11R22.5	02395	14G	8.25	7.50	10.8	41.4	19	12.0	19.3	504	
11R22.5	02392	16H	8.25	7.50	10.8	41.4	19	12.0	19.3	504	
285/75R24.5	02390	14G	8.25	...	10.9	41.4	19	11.8	19.2	503	
11R24.5	02393	14G	8.25	7.50	10.7	43.4	19	11.9	20.0	483	
11R24.5	02394	16H	8.25	7.50	10.7	43.4	19	11.9	20.0	483	

**\* Trailer Use Only**

Yokohama tires are subject to an ongoing development process. Yokohama Tire Corporation reserves the right to change product specifications at any time without notice or obligation. Not all models and sizes available in all locations.



**Yokohama Tire Corporation**

Corporate Headquarters  
P.O. Box 4550  
Fullerton, CA 92834-4550  
800.423.4544 714.870.3800

**Commercial Customer Service**

For Dealer Orders Call: 800.241.7051  
Dealer Fax Orders Call: 800.455.9656 / 770.932.0560

**Consumer Affairs**

800.722.9888

yokohamatire.com

